

## Trus Joist® TJI® Ceiling Joist Supporting Attic Load and Roof Thrust Load

The following information is intended to assist designers in the specification of TJI® for ceiling joist applications supporting both attic load and roof thrust load, as prescribed in 2015/2018/2021 IRC Chapter 8. It is the responsibility of the designer of record to confirm the conditions of the ceiling joist to be within the limitations of the tables provided in this document. For additional design information regarding TJI® joists, reference *Trus Joist® TJI® Joist Specifier's Guide (TJ-4000)*.

### Ceiling Joists Supporting Attic Load and Roof Thrust Load

Table 1 provides maximum clear spans for TJI® ceiling joists supporting “uninhabitable attics with limited storage” or “areas other than sleeping areas” as defined by 2015/2018/2021 IRC Table R301.5 and a roof thrust load based on IRC prescribed connections between roof rafters and ceiling joists. The nailing requirements for the rafter-to-ceiling joist connection are given by 2015 IRC Table R802.5.1(9), 2018 IRC Table R802.5.2, and 2021 IRC Table R802.5.2(1). Prior to fastening the rafter-to-ceiling joist connection, the TJI® joist must be reinforced to accommodate both the thrust load and tapered end cut (see Trus Joist® TJI® Rafter Cut/Thrust Load Reinforcement Detail). For ceiling joists supporting only attic load, reference *Trus Joist® TJI® Ceiling Joist Supporting Attic Load (TB-805)*.

**TABLE 1: TJI® CEILING JOIST SUPPORTING ATTIC LOAD AND ROOF THRUST LOAD<sup>[1][2][3][4]</sup>**

Depth	TJI®	Maximum Clear Span <sup>[5][6][7][8]</sup>							
		20 PSF Live Load / 10 PSF Dead Load				40 PSF Live Load / 10 PSF Dead Load			
		12" o.c.	16" o.c.	19.2" o.c.	24" o.c.	12" o.c.	16" o.c.	19.2" o.c.	24" o.c.
9½"	<b>110</b>	22'-3"	20'-1"	18'-11"	17'-6"	17'-6"	15'-10"	14'-10"	13'-8"
	<b>210</b>	23'-6"	21'-3"	20'-0"	18'-6"	18'-6"	16'-8"	15'-8"	14'-5"
	<b>230</b>	24'-4"	22'-0"	20'-8"	19'-1"	19'-1"	17'-3"	16'-2"	14'-11"
11⅞"	<b>110</b>	26'-7"	24'-1"	22'-6"	20'-1"	20'-11"	18'-11"	17'-5"	15'-6"
	<b>210</b>	28'-1"	25'-5"	23'-10"	22'-0"	22'-1"	19'-11"	18'-8"	17'-0"
	<b>230</b>	29'-0"	26'-3"	24'-8"	22'-9"	22'-9"	20'-7"	19'-4"	17'-10"
	<b>360</b>	30'-10"	27'-11"	26'-2"	24'-3"	24'-3"	21'-11"	20'-6"	18'-11"
	<b>560</b>	35'-6"	32'-1"	30'-2"	27'-11"	27'-11"	25'-2"	23'-7"	21'-10"
14"	<b>110</b>	30'-3"	26'-10"	24'-5"	21'-9"	23'-10"	20'-9"	18'-11"	16'-10"
	<b>210</b>	31'-11"	28'-11"	26'-10"	23'-11"	25'-1"	22'-9"	20'-9"	18'-6"
	<b>230</b>	32'-11"	29'-10"	28'-0"	25'-3"	25'-11"	23'-5"	21'-11"	19'-6"
	<b>360</b>	35'-0"	31'-9"	29'-9"	27'-7"	27'-7"	24'-11"	23'-4"	21'-5"
	<b>560</b>	36'-0" <sup>[9]</sup>	36'-0" <sup>[9]</sup>	34'-3"	31'-8"	31'-8"	28'-7"	26'-10"	24'-9"
16"	<b>110</b>	33'-2"	28'-8"	26'-1"	23'-3"	25'-8"	22'-2"	20'-2"	18'-0"
	<b>210</b>	35'-5"	31'-5"	28'-8"	25'-7"	27'-10"	24'-4"	22'-2"	19'-9"
	<b>230</b>	36'-0" <sup>[9]</sup>	33'-1"	30'-3"	27'-0"	28'-9"	25'-8"	23'-5"	20'-10"
	<b>360</b>	36'-0" <sup>[9]</sup>	35'-2"	33'-0"	30'-6"	30'-6"	27'-7"	25'-10"	21'-5"
	<b>560</b>	36'-0" <sup>[9]</sup>	36'-0" <sup>[9]</sup>	36'-0" <sup>[9]</sup>	35'-1"	35'-1"	31'-8"	29'-9"	25'-2"

[1] Uniform loads only.

[2] Roof thrust load calculated based on 30 PSF roof live/snow load and 10 PSF dead load.

[3] Roof pitch 6:12 to 12:12. Maximum roof overhang is 24".

[4] Struts or posts supporting roof framing or purlin lines must not be braced to joists.

[5] Simple span only.


[6] Minimum bearing length of 2¼" end.

[7] Total load deflection limited to L/240 and live load deflection limited to L/360; assumed no composite action.

[8] For TJI® 110, maximum on-center spacing of bracing is 32" o.c.; for all other TJI® joists, use 36" o.c.

[9] Maximum clear span limited by scope of IRC table.

## Trus Joist® TJI® Rafter Cut/Thrust Load Reinforcement Detail



**TABLE 2: Rafter Cut/Thrust Load Reinforcement**

TJI®	Material	Nail
<b>110</b>	3/4" CDX or OSB	
<b>210</b>	7/8" CDX or OSB	
<b>230</b>	7/8" or 1" net CDX or OSB	20 (0.131" x 2 1/4") or larger, clinched
<b>360</b>		
<b>560</b>	1 1/2" thick TimberStrand® LSL <sup>[1]</sup>	22 (0.131" x 3 1/2") or larger, clinched

[1] TimberStrand® LSL may be re-sawn per [TB-305](#).

**The maximum clear spans in Table 1 consider an axial tension load due to the thrust force resulting from the roof rafter being fastened to the ceiling joist. Reference 2015 IRC Table R802.5.1(9), 2018 IRC Table R802.5.2, or 2021 IRC Table R802.5.2(1) for additional design requirements of rafter-to-ceiling joist connections.**

If you have any questions, please contact  
your Weyerhaeuser representative.